

# AJ&D Chapelhow (Cliburn) Ltd

Crafting fine timber windows and doors since 1961

---

## Sliding Folding Doorsets

### Before Fitting:

- The cill **MUST BE** level and straight along the entire length.
- We **STRONGLY RECOMMEND** that a DPC is fixed to the underside of the cill and the jambs are set Plumb.
- The cill **MUST BE** supported along the entire length to avoid any Operating problems.

### Fitting:

- Make sure the doors are plumb level and square in all directions, Ensure the fixings are made at no more than a metre apart to the head, cill and styles. These **MUST BE STRAIGHT** not up and down, use packers or wedges to straighten if needed.

### Locking System:

- The locking system is our standard 3 point lock – to lock you must apply a little pressure to the door lift the handle upwards and turn the key – to unlock you simply turn the key.

### Hinge instructions:

- Please see our hinge instructions for the 3D hinge which is used at the fixed jamb end and the intermediate hinges.

### Use of Sealant:

- Should you require to use a sealant to the underside of the hardwood cill please ensure any sealant is placed so that it will not block up or interfere with the drainage weep hole.
- **ON NO ACCOUNT** must the front edge of the external face of the cill be sealed.

### PLEASE NOTE:

- It is the responsibility of the contractor / fixer to ensure that the information sheet is handed to the end user.
- For more information please contact us.

T: 01931 585 101 or 01931 714 289

Email: [enquiries@ajdchapelhow.co.uk](mailto:enquiries@ajdchapelhow.co.uk) • [www.ajdchapelhow.co.uk](http://www.ajdchapelhow.co.uk)

LING PARK • CLIBURN • PENRITH • CUMBRIA • CA10 3AL